



5620

8 Mil Matte Polypropylene Film

A water-resistant, durable and economical polypropylene film with a non-glare finish.

- Flat, tear resistant film
- For indoor and outdoor use
- Excellent color brilliance and image definition
- Compatible with latex & EcoSol inks
- Can be hemmed with double-sided banner tape
- Cold lamination use only

Physical Specifications

Basis Weight (grams/m ²):	130
Caliper (mil):	8
Gloss (@ 60°):	2
Whiteness	125

* Values are Target Values

Compatible Ink Type

Compatible With Most Latex, Solvent & Eco Solvent Printers



How to Buy

Email Orders@Permalite.com - For additional product information visit our website www.Permalite.com or contact your Permalite sales representative.

RECOMMENDED STORAGE CONDITIONS

Temperature: 72°F ± 5°F (22°C ± 3°C); Relative Humidity: 35 - 65%; unused portion to original packaging when not in use; Shelf Life: 1 Year under recommended storage conditions





5620R

7.5 Mil Matte Adhesive Polypropylene Film

A water-resistant, durable and economical polypropylene film with a non-glare finish.

- Flat, tear resistant film
- For indoor and outdoor use
- Excellent color brilliance and image definition
- Compatible with latex & EcoSol inks
- Can be hemmed with double-sided banner tape
- Cold lamination use only
- Removable

Physical Specifications

Basis Weight (grams/m ²):	150
Caliper (mil):	7.5
Gloss (@ 60°):	2
Whiteness	125
Adhesive:	Removable

* Values are Target Values

Compatible Ink Type

Compatible With Most Latex, Solvent & Eco Solvent Printers



How to Buy

Email Orders@Permalite.com - For additional product information visit our website www.Permalite.com or contact your Permalite sales representative.

RECOMMENDED STORAGE CONDITIONS

Temperature: 72°F ± 5°F (22°C ± 3°C); Relative Humidity: 35 - 65%; unused portion to original packaging when not in use; Shelf Life: 1 Year under recommended storage conditions



5620P

7.5 Mil Matte Adhesive Polypropylene Film

A water-resistant, durable and economical polypropylene film with a non-glare finish.

- Flat, tear resistant film
- For indoor and outdoor use
- Excellent color brilliance and image definition
- Compatible with latex & EcoSol inks
- Can be hemmed with double-sided banner tape
- Cold lamination use only
- Permanent

Physical Specifications

Basis Weight (grams/m ²):	150
Caliper (mil):	7.5
Gloss (@ 60°):	2
Whiteness	125
Adhesive:	Permanent

* Values are Target Values

Compatible Ink Type

Compatible With Most Latex, Solvent & Eco Solvent Printers



How to Buy

Email Orders@Permalite.com - For additional product information visit our website www.Permalite.com or contact your Permalite sales representative.

RECOMMENDED STORAGE CONDITIONS

Temperature: 72°F ± 5°F (22°C ± 3°C); Relative Humidity: 35 - 65%; unused portion to original packaging when not in use; Shelf Life: 1 Year under recommended storage conditions